


■ 车规抗硫化宽边电极厚膜片式固定电阻器

Anti-Sulfurated Wide Terminal Type Thick Film Chip Fixed Resistor



◆ 特点 Features

- * 采用宽边电极设计实现高功率性能
Wide-edge electrode design is used to realize high power performance.
- * 符合AEC- Q200汽车标准相关条款 Compliant with AEC-Q200 standard
- * 电性能稳定，可靠性高 Stable electrical capability, high reliability.
- * 具有优越的抗硫化性能 With excellent sulfuration-resistant performance
- * 符合RoHS指令要求 Compliant with RoHS Directive
- * 符合无卤素要求 Halogen free requirement

◆ 应用领域 Application

车用仪表、车灯驱动模块、车载信息系统、遥控钥匙、汽车辅助驾驶系统、车身控制器等。
Vehicle instrument, Lamp driving module, On-board information system, Remote control key,
Driving aid system, Body controller, etc.

◆ 型号表示方法 Part Number

AH	J	1225	W	R120	F	T			
产品代号 Product Code	额定功率代号 Rated Power Code		电阻温度系数代号 T.C.R Code			电阻值误差精度代号 Resistance Tolerance Code		包装方式代号 Packaging Style Code	
车规 抗硫化 宽边电极 厚膜片式 固定 电阻器 Anti-sulfurated Wide Terminal Type Thick Film Chip Fixed Resistor Automotive Grade	代 号 Code	额定 功率 Rated Power	代 号 Code	型 号 Type	T.C.R (ppm/°C)	代 号 Code	误差 精度 Tolerance	代 号 Code	包 装 方法 Packaging Style
	R	1/3W			K ±100				
	G	1/2W	0508	0508	J ±150		F ±1%		
	J	1W			W ±200				
	L	2W	0612	0612	L ±250		G ±2%		
	N	3W			B ±300				
			1225	1225	M ±500		J ±5%		
					Q ±800				
电阻值代号 Resistance Value Code						单位 Ω, 小数点用R表示; 单位 mΩ, 小数点用M表示; Units:Ω Decimal point should be expressed by “R” ; Units: mΩDecimal point should be expressed by ‘M’ 例如 Example: 103=10KΩ(E-24) 1R0=1.0Ω(E-24) 1003=100KΩ(E-96) 当阻值小于1Ω用四位 数表示: R470=470mΩ R050=50mΩ R047=47mΩ			
						编带 包装 Tape & Reel			

注：1、不同厂家的超低阻产品其工艺及技术参数可能会略有差异，建议客户索样评估使用的可行性；不同厂家的超低阻产品不建议直接替换使用，我司不承担因直接替换使用而带来的经济损失。


The process and technical parameters of ultra-low resistance products from different manufactures may be slightly different, so it is suggested that customers ask for samples to evaluate the feasibility of use; the ultra-low resistance products from different manufactures are not recommended to be replaced directly, and our company will not bear the economic losses caused by the direct replacement.

2、阻值 $\leq 50\text{m}\Omega$ 的超低阻产品，如果必须选用厚膜超低阻产品，选型时请联系原厂。

For the resistance value $<50m\ \Omega$, if thick ultra-low resistance products must be selected, please contact our customer service team for selection.


◆ 结构 Construction

$R \geq 100m\Omega$ 采用正面贴装结构 Positive surface mounted structure



- ① 陶瓷基板 Ceramic Substrate
- ② 背电极 Bottom Electrode
- ③ 面电极 Top Electrode
- ④ 电阻体 Resistor Layer
- ⑤ 一次保护 Primary Overcoat
- ⑥ 二次保护 Secondary Marking
- ⑦ 端电极 Edge Electrode
- ⑧ 中间电极 Barrier Layer
- ⑨ 外部电极 External Electrode

$R < 100m\Omega$ 采用反面贴装结构 Reverse surface mounted structure



- ① 陶瓷基板 Ceramic Substrate
- ② 面电极 Top Electrode
- ③ 背电极 Bottom Electrode
- ④ 电阻体 Resistor Layer
- ⑤ 一次保护 Primary Overcoat
- ⑥ 二次保护 Secondary Marking
- ⑦ 端电极 Edge Electrode
- ⑧ 中间电极 Barrier Layer
- ⑨ 外部电极 External Electrode


◆ 规格尺寸 Dimensions

型号 Type	尺寸 Dimensions(mm)						
	L	W	t	a	b	* c	* d
0508	1.25 ± 0.10	2.00 ± 0.15	0.55 ± 0.10	0.30 ± 0.20	0.30 ± 0.20	0.30 ± 0.20	0.30 ± 0.20
0612	1.60 ± 0.20	3.20 ± 0.15	0.55 ± 0.10	0.30 ± 0.20	0.35 ± 0.20	0.35 ± 0.20	0.30 ± 0.20
1225	3.20 ± 0.20	6.40 ± 0.20	0.55 ± 0.10	0.40 ± 0.20	0.75 ± 0.20	0.75 ± 0.20	0.40 ± 0.20
1225*	3.20 ± 0.20	6.40 ± 0.20	0.55 ± 0.10	0.40 ± 0.20	1.05 ± 0.20	0.75 ± 0.20	0.40 ± 0.20

注：1225*表示1225-3W特殊功率产品

Note: 1225* indicates the special power product of 1225-3W.

◆ 负荷下降曲线 Derating Curve



注：当电阻使用的环境温度超过70℃时，其额定负荷(额定功率或额定电流)按上述曲线下降。

Note: For resistors operated in ambient over 70℃, rated load (rated power or rated current) shall be derated in accordance with the above figure.

◆ 额定值 Ratings

型 号 Type	70℃下额定功率 Rating Power	元件极限电流 Limiting Element Current (A)	最大过负荷电流 Max. Overload Current (A)	元件极限电压 Limiting Element Voltage (V)	最大过负荷电压 Limiting Element Voltage (V)	阻 值 范 围 Resistance Range
0508	1/3、1/2	5.7	14.25	/	/	$0.01\Omega \leq R < 1\Omega$
0612	1	10	25	/	/	$0.01\Omega \leq R < 1\Omega$
1225	2、3	14.1	35.25	/	/	$0.01\Omega \leq R < 1\Omega$
0508	1/3、1/2	/	/	150	200	$1\Omega \leq R \leq 10M\Omega$
0612	1	/	/	200	400	$1\Omega \leq R \leq 10M\Omega$
1225	2、3	/	/	200	400	$1\Omega \leq R \leq 10M\Omega$
注Note:	1、电流为直流或交流有效值。 Current of DC or AC RMS value. 2、 $0.01\Omega \leq R < 1\Omega$: $I = \sqrt{P/R}$ 或元件极限电流两者中的较小值。 $I = \sqrt{P/R}$ or Limiting element current whichever is lower. $1\Omega \leq R \leq 10\Omega$: $E = \sqrt{P \times R}$ 或元件极限电压两者中的较小值。 $E = \sqrt{P \times R}$ or Limiting element voltage whichever is lower. I: 额定电流 Rated current(A) E: 额定电压 Rated voltage (V) P: 额定功率 Rated power(W) R: 标称阻值 Normal resistance(Ω)					

◆ 额定值 Ratings

型 号 Type	70℃下额定功率 Rating Power at 70℃ (W)	阻 值 范 围 Resistance Range	电阻温度系数 T.C.R (PPM/℃)	代号 Code
			$\pm 1\% \pm 2\% \pm 3\% \pm 5\%$	
0508	1/3、1/2	$0.01\Omega \leq R < 0.02\Omega$	± 800	Q
		$0.02\Omega \leq R < 0.10\Omega$	± 300	B
		$0.10\Omega \leq R < 1\Omega$	± 200	W
		$1\Omega \leq R < 10\Omega$	± 150	J
		$10\Omega \leq R < 1M\Omega$	± 100	K
		$1M\Omega \leq R \leq 10M\Omega$	± 250	L
0612	1	$0.01\Omega \leq R < 0.03\Omega$	± 800	Q
		$0.03\Omega \leq R < 0.10\Omega$	± 300	B
		$0.10\Omega \leq R < 1\Omega$	± 200	W
		$1\Omega \leq R < 10\Omega$	± 150	J
		$10\Omega \leq R < 1M\Omega$	± 100	K
		$1M\Omega \leq R \leq 10M\Omega$	± 250	L
1225	2、3	$0.01\Omega \leq R < 0.06\Omega$	± 500	M
		$0.06\Omega \leq R < 0.25\Omega$	± 200	W
		$0.25\Omega \leq R < 1\Omega$	± 100	K
		$1\Omega \leq R < 15\Omega$	± 150	J
		$15\Omega \leq R < 1M\Omega$	± 100	K
		$1M\Omega \leq R \leq 10M\Omega$	± 250	L

◆特性 Characteristics

项目 Item	标准 Specifications	测试方法 (IEC60115-1) Test Methods (IEC60115-1)
可焊性 Solderability	可焊面积 ≥ 95% 95% Cover Min	AEC-Q200 Test 18/IEC 60115-1 4.17 245°C ± 5°C 锡槽, 保持3s ± 0.3s. Lead-free solder bath at 245°C ± 5°C for 3s ± 0.3s.
耐焊接热 Resistance to Soldering Heat	无可见损伤 No mechanical damage $R < 1\Omega$ 1%: $\Delta R \leq \pm (0.5\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1%: $\Delta R \leq \pm (0.5\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$	AEC-Q200 Test 15/IEC 60115-1 4.18 270°C ± 5°C 锡槽, 保持10s ± 1s. Lead-free solder bath at 270°C ± 5°C for 10s ± 1s.
基板弯曲试验 Substrate Bending Test	无可见损伤 No mechanical damage $R < 1\Omega$ 1%: $\Delta R \leq \pm (0.5\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1%: $\Delta R \leq \pm (0.5\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$	AEC-Q200 Test 21/IEC 60115-1 4.33 弯曲距离(Bending distance): 0508:3mm;0612:2mm;1225: 1mm 保持时间(Duration): 60s ± 5s.
电阻温度系数 T.C.R	在规定值内 Within specified T.C.R	AEC-Q200 Test 19/IEC 60115-1 4.8 +20°C/-55°C/+20°C/+125°C/+20°C
短时间过负载 Short Time Overload	无可见损伤 No mechanical damage $R < 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.05\Omega)$	IEC 60115-1 4.13 2. 5倍额定电流 (电压) 或过大负荷电流 (电压) (取较小值), 持续5秒。 2.5 times rated voltage or max. overload current whichever is lower for 5s.
高温存储 High Temperature Exposure (Storage)	无可见损伤 No mechanical damage $R < 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.05\Omega)$	AEC-Q200 Test 3/MIL-STD-202 Method 108 温度155°C, 持续时间1000h, 不通电。 1000 hrs. @ T=155° C. Unpowered.
低温负载 Operation at Low Temperature	无可见损伤 No mechanical damage $R < 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (2.0\%R + 0.05\Omega)$	IEC 60115-1 4.36 -55°C ± 5°C, 无负载1小时, 额定电压或元件极限电压 (取较小值) 45分钟, 无负载15分钟。 -55°C ± 5°C, 1h without load, rated voltage (current) or limiting element voltage (current) whichever is lower for 45min, 15min without load.
耐溶剂 Component Solvent Resistance	无可见损伤 No mechanical damage $R < 1\Omega$ $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$	AEC-Q200 Test 12/MIL-STD-202 Method 215 异丙醇(IPA), 23°C ± 5°C, 浸10小时。 iso-propyl alcohol(IPA), 23°C ± 5°C, 10h.
抗硫化性能 Sulfuration-Resistant	无可见损伤 No mechanical damage $R < 1\Omega$: $\Delta R \leq \pm (5.0\%R + 0.5m\Omega)$ $R > 1\Omega$: $\Delta R \leq \pm (5.0\%R + 0.05\Omega)$	切削油: 硫磺粉, 恒温: 105°C ± 3°C, 放置时间: 1000小时 Cutting oil : sulphur powder, constant temperature: 105°C ± 3°C, for 1000h.
工作寿命 Operational Life	无可见损伤 No mechanical damage $R < 1\Omega$ 1.0%: $\Delta R \leq \pm (1.0\%R + 0.5m\Omega)$ 2%、5%: $\Delta R \leq \pm (3.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1.0%: $\Delta R \leq \pm (1.0\%R + 0.05\Omega)$ 2%、5%: $\Delta R \leq \pm (3.0\%R + 0.05\Omega)$	AEC-Q200 Test 8/MIL-STD-202 Method108 125°C ± 2°C, 1000小时, 额定电流 (电压) 或元件极限电流 (电压) (取较小值), 通1.5小时/断0.5小时。 125°C ± 2°C, 1000h, rated voltage or limiting element voltage whichever is lower for 1.5h ON/0.5h OFF.


◆ 特性 Characteristics

(续上页 Continue)

项目 Item	标准 Specifications	测试方法 (IEC60115-1) Test Methods (IEC60115-1)
机械冲击 Mechanical shock	无可见损伤 No mechanical damage $R < 1\Omega$ $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ $\Delta R \leq \pm(1.0\%R + 0.05\Omega)$	AEC-Q200 Test 13/MIL-STD-202 Method 213 正半弦波, 峰值加速度100g/S, 脉冲持续时间6mS, 三轴六向各3次, 共18次。 Positive half wave, peak acceleration:100g S,pulse duration: three axis six to each 3 times, a total of 18 times.
振动 Vibration	无可见损伤 No mechanical damage $R < 1\Omega$ $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ $\Delta R \leq \pm(1.0\%R + 0.05\Omega)$	AEC-Q200 Test 14/MIL-STD-202 Method 204 频率: 10Hz~2000Hz; 加速度: 5g' S; 一个循环20分钟; X、Y、Z三个方向每个方向12个循环, 共36个循环。 Frequency:10Hz~2000Hz,acceleration:5g S, a loop 20min, X,Y,Z three directions, each direction 12 cycles,36 cycles.
ESD静电放电 Electrostatic Discharge	无可见损伤 No mechanical damage $R < 1\Omega$ $\Delta R \leq \pm(3.0\%R + 0.5m\Omega)$ $R > 1\Omega$ $\Delta R \leq \pm(3.0\%R + 0.05\Omega)$	AEC-Q200 Test 17/AEC-Q200-002 人体模式, 每隔电极承受两次放电, 正、负极性各1次。 0508:1.5KV;0612、1225:2KV Human Body Model,1 pos. + 1 neg discharge.
可燃性 Flammability	不完全燃尽, 薄垫纸应不被引燃, 松木板应不被烤焦碳化 No ignition of the tissue paper or scorching of the pinewood board	AEC-Q200 Test 20/UL-94 V-0或 V-1可接受。不需要电气测试。 V-0 or V-1 are acceptable. Electrical test not required.
端子强度 Terminal Strength	无可见损伤 No mechanical damage $R < 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.05\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.05\Omega)$	AEC-Q200 Test 22/AEC Q200-006 施加力: 17.7N, 保持60s $\pm 1s$ 。 Applying force 17.7N for 60s $\pm 1s$.
阻燃性 Flame Retardanc	不可燃 Not flame	AEC-Q200 Test 24/AEC-Q200-001 9Vdc到 32Vdc (钳位电流高达 500A)、增量为 1.0Vdc 的电压。 每种电压等级最少施加1 小时。 Subjected to voltage from 9.0 to 32.0 VDC (current clamped up to 500A),and each voltage level shall be increased in 1.0 VDC for one hour minimum.
温度循环 Temperature Cycling	无可见损伤 No mechanical damage $R < 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.05\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.05\Omega)$	AEC-Q200 Test 4/JESD22 Method JA-104 -55℃~-125℃, 高、低温下暴露时间各30min, 转换时间: $\leq 1min$, 循环次数: 1000次。 -55℃(30min)~normal temperature($\leq 1min$)~125℃(30min) , 1000 cycles.
高温高湿 Biased Humidity	无可见损伤 No mechanical damage $R < 1\Omega$ $\Delta R \leq \pm(3.0\%R + 0.5m\Omega)$ $R > 1\Omega$ $\Delta R \leq \pm(3.0\%R + 0.05\Omega)$	AEC-Q200 Test 7/MIL-STD-202 Method 103 温度85℃, 湿度85%的条件下施加10%额定功率(电流) 的电压值或元件极限电压(取较小值), 放置1000小时。 85° C/85%RH. 1000 hours, Apply 10% of operating power(current) or limiting element voltage whichever is lower.
热冲击 Thermal Shock	无可见损伤 No mechanical damage $R < 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ $R > 1\Omega$ 1.0%; $\Delta R \leq \pm(0.5\%R + 0.05\Omega)$ 2%, 5%; $\Delta R \leq \pm(1.0\%R + 0.05\Omega)$	AEC-Q200 Test 16/MIL-STD-202 Method 107 -55℃(15分钟)~常温(≤ 20 秒)~155℃(15分钟), 300个循环。 -55℃(15min)~normal temperature($\leq 20s$)~155℃(30min) , 300 cycles.

◆ 推荐焊盘尺寸 Recommend Solder Pad Size

单位 unit: mm



型号Type	A	B	C
0508	0.6	2.2	2.0
0612	0.6	2.9	3.3
1225	1.4	4.5	6.4


◆ 包 装 Packaging:

包装方式见附录 Packaging can refer to the Appendix.

附录 Appendix

◆ 推荐焊盘尺寸 Recommend Solder Pad Size


- 片式固定电阻器 Chip fixed resistor



单位 unit: mm

厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor			
型号Type	A	B	C
01005	0.17 ± 0.03	0.60 ± 0.03	0.22 ± 0.03
0201	0.23 ± 0.05	0.84 ± 0.05	0.38 ± 0.05
0402	0.45 ± 0.05	1.45 ± 0.05	0.60 ± 0.05
0603	0.80 ± 0.05	2.50 ± 0.05	0.95 ± 0.05
0805	1.05 ± 0.1	3.25 ± 0.1	1.40 ± 0.1
1206	1.90 ± 0.1	4.50 ± 0.1	1.75 ± 0.1
1210	2.00 ± 0.1	4.60 ± 0.1	2.70 ± 0.1
2010	3.50 ± 0.1	6.50 ± 0.1	2.70 ± 0.1
2512	4.80 ± 0.1	7.80 ± 0.1	3.40 ± 0.1
2512 (2W)	2.70 ± 0.1	7.80 ± 0.1	3.60 ± 0.1

- 厚膜片式网络电阻器 Thick film chip network resistor



单位 unit: mm


型号 Type	A	B	Q1	Q2	Q3
RH-MY04	0.30 ± 0.05	0.90 ± 0.05	0.30 ± 0.05	0.20 ± 0.05	/
RH-MY08 RCMY08	0.30 ± 0.05	0.90 ± 0.05	0.20 ± 0.05	0.20 ± 0.05	0.20 ± 0.05
RCMT08	0.38 ± 0.05	1.60 ± 0.05	0.40 ± 0.05	0.20 ± 0.05	0.30 ± 0.05
RCML08	0.80 ± 0.05	2.70 ± 0.05	0.60 ± 0.05	0.40 ± 0.05	0.40 ± 0.05

◆ 包装 Packaging

● 纸带编带 Paper Taping

适用于01005、0201、0402、RH-MY04、RH-MY08、RCMY08、RCMT08：

For 01005、0201、0402、RH-MY04、RH-MY08、RCMY08、RCMT08：



单位 unit: mm


型号 Type	A	B	W	F	E
01005	0.45±0.02	0.25±0.02	8.00±0.02	3.50±0.05	1.75±0.05
0201	0.70±0.10	0.40±0.10	8.00±0.20	3.50±0.05	1.75±0.10
0402	1.15±0.10	0.65±0.10	8.00±0.20	3.50±0.05	1.75±0.10
RH-MY04	0.97±0.05	0.77±0.05	8.00±0.20	3.50±0.05	1.75±0.10
RH-MY08 RCMY08	1.57±0.05	0.77±0.05	8.00±0.20	3.50±0.05	1.75±0.10
RCMT08	2.20±0.10	1.20±0.10	8.00±0.20	3.50±0.05	1.75±0.10

单位 unit: mm

型号 Type	P	P0	P1	ΦD0	T1	T
01005	2.00±0.05	4.00±0.10	2.00±0.05	1.55±0.02	0.17±0.02	0.31±0.02
0201	2.00±0.05	4.00±0.10	2.00±0.05	1.50±0.10	0.28±0.04	0.42±0.05
0402	2.00±0.05	4.00±0.10	2.00±0.05	1.50±0.10	/	0.44±0.05
RH-MY04	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10
RH-MY08 RCMY08	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10
RCMT08	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10

适用于0603、0805、1206、1210、RCML08：

For 0603、0805、1206、1210、RCML08：



单位 unit: mm

型号 Type	A	B	W	F	E
0603	1.80 ± 0.10	1.05 ± 0.10	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10
0805	2.30 ± 0.10	1.50 ± 0.10	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10
1206	3.50 ± 0.20	1.90 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10
1210	3.50 ± 0.20	2.80 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10
RCML08	3.50 ± 0.20	1.90 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10


单位 unit: mm

型号 Type	P	P0	P1	$\Phi D0$	T	
					厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor	合金片式固定电阻 Metal Foil Resistor
0603	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 ± 0.10	0.60 ± 0.10	0.75 ± 0.10
0805	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 ± 0.10	0.75 ± 0.10	0.95 ± 0.10
1206	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 ± 0.10	0.75 ± 0.10	0.95 ± 0.10
1210	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 ± 0.10	0.75 ± 0.10	---
RCML08	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 ± 0.10	0.75 ± 0.10	---

● 塑料带编带 Embossed Taping

适用于2010、2512:

For 2010、2512:




单位 unit: mm

型号 Type	A0	B0	W	F	E	t
2010	5.50 ± 0.15	2.82 ± 0.15	12.00 ± 0.10	5.50 ± 0.10	1.75 ± 0.10	0.25 ± 0.05
2512	6.78 ± 0.15	3.45 ± 0.15	12.00 ± 0.10	5.50 ± 0.10	1.75 ± 0.10	0.25 ± 0.05

单位 unit: mm

型号 Type	P	P0	P1	$\Phi D0$	$\Phi D1$	K0	
						厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor	合金片式固定电阻 Metal Foil Resistor
2010	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	$1.50 \pm 0.10/-0$	1.50 ± 0.10	0.84 ± 0.10	0.84 ± 0.10
2512	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	$1.50 \pm 0.10/-0$	1.50 ± 0.10	0.81 ± 0.10	1.00 ± 0.10

● 卷盘 Reel



单位 unit: mm

型号 Type	M	W	T	A	B	C	D
01005、0201 0402、0603 0805、1206 1210、RCMY08、 RCMT08、RCML08、 RH-MY04、 RH-MY08	178±2.0	9.5±1.0	12.5±1.5	2.0±0.5	13.0±0.5	21.0±0.5	58.0±2.0
2010、2512	178±2.0	13.0±0.5	15.5±1.5	2.0±0.5	13.0±0.5	21.0±0.5	57.0±2.0


● 编带包装能力 Taping Ability

面带拉力 Top tape peel strength

面带拉力强度为11~70g(0.1N~0.7N) , 速度: 300mm/min,经下列试验后不允许有破裂断带现象。

Peel strength is 11~70g (0.1N~0.7N),with speed of 300mm/min,and should not have flash and tear after peeling.

测试方法Test method:



电阻松动自如, 无粘面胶带、底胶带现象。

Resistor is free, no sticking to top tape and bottom tape.

电阻易从纸带中取出, 且晶片孔无机械损伤。

Resistor is easy to take out from carrier tape and chip hole have no mechanical damage.

● 包装数量 Packaging Quantity

包装方法 Packaging style	编带 Tape & reel					塑料袋散装 Case		
型号 Type	01005	0201	0402、 RH-MY04、 RH-MY08、 RCMY08、 RCMT08	0603、0805 1206、1210 RCML08	2010 2512	01005 0201 0402	0603、0805 1206、 RCMY08、RCMT08、 RCML08	1210 2010 2512
数量 Quantity(pcs)	20000	15000	10000	5000	4000	≤50000	≤10000	≤4000

◆ IEC E-24、E-96系列电阻值代码对照表

IEC E-24、E-96 Series Resistance Cross-reference List

● E-24 系列 E-24 series ($\times 10^n \Omega$)

(单位 unit: 0.001 Ω 、0.01 Ω 、0.1 Ω 、1 Ω 、10 Ω 、100 Ω 、1k Ω 、10k Ω 、100k Ω 、1M Ω 、10M Ω 、100M Ω 、1000M Ω)

表一 Table One:

1.0	1.5	2.2	3.3	4.7	6.8
1.1	1.6	2.4	3.6	5.1	7.5
1.2	1.8	2.7	3.9	5.6	8.2
1.3	2.0	3.0	4.3	6.2	9.1

● E-96系列 E-96 series ($\times 10^n \Omega$)

(单位unit: 0.001 Ω 、0.01 Ω 、0.1 Ω 、1 Ω 、10 Ω 、100 Ω 、1k Ω 、10k Ω 、100k Ω 、1M Ω 、10M Ω 、100M Ω 、1000M Ω)

表二 Table Two:

1.00	1.33	1.78	2.37	3.16	4.22	5.62	7.50
1.02	1.37	1.82	2.43	3.24	4.32	5.76	7.68
1.05	1.40	1.87	2.49	3.32	4.42	5.90	7.87
1.07	1.43	1.91	2.55	3.40	4.53	6.04	8.06
1.10	1.47	1.96	2.61	3.48	4.64	6.19	8.25
1.13	1.50	2.00	2.67	3.57	4.75	6.34	8.45
1.15	1.54	2.05	2.74	3.65	4.87	6.49	8.66
1.18	1.58	2.10	2.80	3.74	4.99	6.65	8.87
1.21	1.62	2.15	2.87	3.83	5.11	6.81	9.09
1.24	1.65	2.21	2.94	3.92	5.23	6.98	9.31
1.27	1.69	2.26	3.01	4.02	5.36	7.15	9.53
1.30	1.74	2.32	3.09	4.12	5.49	7.32	9.76

● E-96系列0603型号《乘数代码对照表》及《电阻值代码对照表》

E-96 series(0603)《multiplied Cross-reference List》and《Resistance Cross-reference List》

表三 Table Three:

乘数multiplied	$\times 10^0$	$\times 10^1$	$\times 10^2$	$\times 10^3$	$\times 10^4$	$\times 10^5$	$\times 10^6$	$\times 10^7$	$\times 10^{-1}$	$\times 10^{-2}$	$\times 10^{-3}$
代码 code	A	B	C	D	E	F	G	H	X	Y	Z

表四 Table Four:

代号 Code	E-96系列电阻 E-96 resistance	代号 Code	E-96系列电阻 E-96 resistance	代号 Code	E-96系列电阻 E-96 resistance	代号 Code	E-96系列电阻 E-96 resistance
01	100	25	178	49	316	73	562
02	102	26	182	50	324	74	576
03	105	27	187	51	332	75	590
04	107	28	191	52	340	76	604
05	110	29	196	53	348	77	619
06	113	30	200	54	357	78	634
07	115	31	205	55	365	79	649
08	118	32	210	56	374	80	665
09	121	33	215	57	383	81	681
10	124	34	221	58	392	82	698
11	127	35	226	59	402	83	715
12	130	36	232	60	412	84	732
13	133	37	237	61	422	85	750
14	137	38	243	62	432	86	768
15	140	39	249	63	442	87	787
16	143	40	255	64	453	88	806
17	147	41	261	65	464	89	825
18	150	42	267	66	475	90	845
19	154	43	274	67	487	91	866
20	158	44	280	68	499	92	887
21	162	45	287	69	511	93	909
22	165	46	294	70	523	94	931
23	169	47	301	71	536	95	953
24	174	48	309	72	549	96	976

◆ 厚膜电阻阻值代码及标记规则

Description for Resistance Value Code and Marking of Thick Film Chip Resistor

● 阻值代码 Resistance Value Code

所有厚膜电阻的阻值代码与其标记是相对应的。


All the resistance value code of thick film chip resistor is corresponding with the marking .

● 标记 Marking

* E-24系列(≥ 0603 、 $\geq \pm 5\%$): 采用三位数字表示, 前二位表示电阻值有效数字, 第三位表示乘以10的次方数。

E-24 series: Express resistance value on the glass side with three digits, the first tow digits should be significant and the third one denote number of zeros.

例 For example:



30K Ω



33 Ω

* E-24系列 (0603、 $\leq \pm 1\%$): 在三位数字标记下方增加下横线识别。

E-24 series(0603、 $\leq \pm 1\%$): Three digits with one short bar under marking letter.

例 For example:



* E-96系列和E24系列 (≥ 0805 、 $\leq \pm 1\%$):

▲ 采用四位数字表示, 前三位表示电阻值有效数字, 第四位表示乘以10的次方数。

E-96 series & E-24 series (≥ 0805 、 $\leq \pm 1\%$):

Express the resistance value with four digits, the first three digits are significant figures and the fourth de notes the number of zeros.

例 For example:



100K Ω

* E-96系列 (0603、 $\leq \pm 1\%$):

▲ 采用三位代码表示, 前二位表示E-96系列阻值代码, 后一位字母表示乘数代码 (见表三和表四)。

Express the resistance value with three code, the first two digit code denote the resistance of E-96 series, and the third code of letter denote the multiplier (see the table three and four).

例 For example:



2M Ω

* 小数点以 “R” 表示 The decimal point should be expressed by “R” .

例 For example:



5.6 Ω



22 Ω

* 跨接电阻以 “0” 表示 The jumper should be expressed by “0”

例 For example:



0 Ω



0 Ω

* ≤ 0402 产品不作标记 For the chip resistor(≤ 0402), there is no mark on the glass side.

例 For example:



* 非IEC标准系列的电阻值标记表示方法: 一般以最接近IEC E24系列标称阻值的标记表示方法。

For the resistance which don't belong to IEC serial, use the resistance of IEC serial which is most close to the required resistance of non-IEC serial for replacement.

* 客户对标记有特殊要求时, 则按照协商的结果印刷标记。

To get agreement by both party if there special requirement for the marking.

◆ 薄膜电阻阻值代码及标记规则

Description for Resistance Value Code and Marking of Thin Film Chip Resistor

● 阻值代码 Resistance Value Code

所有薄膜电阻全尺寸统一采用四位数阻值代码表示。

All resistance value code of thin film chip resistor used four digits.

例 Example

TD03G4701BT

四位数代号表示，如：4701=4.7K Ω ；1R50=1.5 Ω

To use four digits code represent resistance value ,

例 Example 4701=4.7K Ω ；1R50=1.5 Ω

● 标记 Marking

* 当阻值同时存在于E24和E96系列时，优先采用E96系列。

When resistance value belongs to E24 as well as E96 series, we suggest preferentially use E96 series.

例 Example 10K=1002, $\neq$ 103

* $\geq$ 0805 产品标记 For the chip resistor ($\geq$ 0805):

▲ 印刷四位数字代码；

Express the resistance value with four digits code;

例 Example

 100K Ω

* 0603标记 Marking for 0603 Size Resistor

▲ 0603-E96系列：印刷三位字母代码；

For resistance value belongs to E96 series, express the resistance value with three digits code.

例 Example

 2M Ω

▲ 0603-E24系列：印刷三位数字代码；

For resistance value belongs to E24 series, express the resistance value with three digits code.

例 Example

 30K Ω

* ▲ 小数点以"R"表示 The decimal point should be expressed by"R".

例 Example

 5.6 Ω

* $\leq$ 0402产品：不作标记 For the chip resistor ($\leq$ 0402), there is no mark on the glass side.

例 Example



◆ 电流检测电阻阻值代码及标记规则

Description for Resistance Value Code and Marking of Current Sensing Thick Film Chip Resistor

● 阻值代码 Resistance Value Code

所有电流检测电阻全尺寸 统一采用四位数阻值代码表示。

All resistance value code of current sensing thick film chip resistor used four digits.

例 Example

RBF03MR010FT

四位代码表示，如：R010=10mΩ；30M1=30.1mΩ

To use four digits code represent resistance value，

例 Example R010=10mΩ；30M1=30.1mΩ

● 标记 Marking

* E-24和E-96系列(≥0805、≤±5%)：采用四位标记代码。

For the chip resistor (≥0805、≤±5%)，when resistance value belongs to E24 and E96 series, we suggest preferentially use four digits.

标记代码 Mark Code	阻值范围 Resistance Value	示例 Sample
R00X	1mΩ ≤ R ≤ 9mΩ	R005=5mΩ
R0XX	10mΩ ≤ R ≤ 99mΩ	R033=33mΩ
RXXX	100mΩ ≤ R ≤ 999mΩ	R100=100mΩ
XMXX	1mΩ < R < 10mΩ (包含小数点后两位有效数字) (Contains two significant digits after the decimal point.)	5M10=5.1mΩ
XXMX	10mΩ < R < 100mΩ (包含小数点后一位有效数字) (Contains one significant digit after the decimal point.)	30M1=30.1mΩ

* E-24和E-96系列(0603、≤±5%)：采用三位标记代码。

For the chip resistor (0603、≤±5%)，when resistance value belongs to E24 and E96 series, we suggest preferentially use three digits.

标记代码 Mark Code	阻值范围 Resistance Value Range	示例 Sample
V0X	1mΩ ≤ R ≤ 9mΩ	V05=5mΩ
VXX	10mΩ ≤ R ≤ 99mΩ	V33=33mΩ
RXX	100mΩ ≤ R ≤ 999mΩ	R10=100mΩ
XXM	1mΩ < R < 10mΩ (包含小数点后一位有效数字) (Contains one significant digit after the decimal point.)	5M1=5.1mΩ

* ≤0402产品不印刷标记。

For the chip resistor (≤0402)，there is no mark on the glass side.

* 非IEC标准系列的电阻值标记表示方法：一般以最接近IEC E24系列标称阻值的标记表示方法。

For the resistance which don't belong to IEC serial, use the resistance of IEC serial which is most close to the required resistance of non-IEC serial for replacement.

* 客户对标记有特殊要求时，则按照协商的结果印刷标记。

To get agreement by both party if there special requirement for the marking.

◆片式电阻器使用说明 Chip Resistor Instructions for Use

● 本产品在以下特殊环境下应用，性能可能会受到影响：

- 1、在各种类型的液体，包括水、油、化学品、有机溶剂的使用。
- 2、在户外直接暴露在阳光的地方，或在灰尘多的地方使用。
- 3、在产品暴露的地方，有海风或腐蚀性气体，包括氯气、硫化氢、氨气、二氧化硫、二氧化氮等。
- 4、在产品暴露于静电或电磁波的地方使用。
- 5、在产生热量的部件、塑料线，或其他易燃物品附近使用。
- 6、在用树脂或其他涂层材料密封产品的情况下使用。
- 7、焊接后使用不洁焊料或使用水或水溶性清洗剂清洗产品。
- 8、片状电阻器的基材是氧化铝。由于和安装基板的热膨胀系数不同，在反复施加提供热循环等热应力时，接合部的焊锡（焊缝部）有时会发生裂纹。如果环境温度反复发生很大的变动，并且载荷反复进行ON/OFF，则需要注意龟裂的发生。因热应力而发生的龟裂，取决于所安装的焊盘的大小、焊锡量、安装基板的散热性等，因此在环境温度有很大的变化或载荷ON/OFF的条件下使用时，请充分注意以进行设计。

◆ Application of the products in a special environment can deteriorate product performance:

- 1、Use in various types of liquid, including water, oils, chemicals, and organic solvents.
- 2、Use outdoors where the products are exposed to direct sunlight, or in dusty places.
- 3、Use in places where the products are exposed to sea winds or corrosive gases, including Cl_2 , H_2S , NH_3 , SO_2 , and NO_2 etc.
- 4、Use in places where the products are exposed to static electricity or electromagnetic waves.
- 5、Use in proximity to heat-producing components, plastic cords, or other flammable items.
- 6、Use involving sealing or coating the products with resin or other coating materials.
- 7、Use involving unclean solder or use of water or water-soluble cleaning agents for cleaning after soldering.
- 8、The substrate of chip resistors is alumina. Cracks may occur at the connection of solder (solder fillet portion) due to the difference of the coefficient of thermal expansion from a mounting board when heat stress like heat cycle, etc. are repeatedly given to them. Care should be taken to the occurrence of the cracks when the change in ambient temperature or ON/OFF of load is repeated. The occurrence of the crack by heat stress may be influenced by the size of a pad, solder volume, heat radiation of mounting board etc., so please pay careful attention to designing when a big change in ambient temperature and conditions for use like ON/OFF of load can be assumed.

◆ 产品使用注意事项



- 1、避免采用超过正常额定功率的功率，超过额定功率的稳态负载条件下可能会对产品性能和可靠性产生负面影响。
- 2、用镊子拿起产品时要小心，有可能会将保护或电阻体夹碎。
- 3、手动安装产品时，烙铁头勿触碰产品。
- 4、贮存条件：温度 $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$ ，相对湿度30%~70%。
建议在符合上述储存条件下六个月内使用。
- 5、用于车载设备、医疗设备、航空设备以及其它涉及人身安全、或可能引起重大损失的设备上时，请务必事先与我公司联系。这些产品在这类用途中出现故障或失灵可能导致人身事故或严重损坏。

◆ Precautions on use of products

- 1、Avoid applying power exceeding normal rated power, exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.
- 2、Be careful when pick up the products with tweezers. There may be a care that the overcoat and / or the body can be chipped.
- 3、Soldering tip shall not touch the product when install product manually.
- 4、Storage conditions: T: $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, RH: 30% ~ 70%.
The products are suggested to be used within six months when received, and the storage condition mentioned above should be followed.
- 5、Contact our sales representatives before you use our products for applications including automotive, medical equipment and aerospace equipment. Malfunction or failure of the products in such applications may cause loss of human life or serious damage.

◆ 焊接 Soldering

- 推荐的回流焊曲线 Recommended reflow profile
- 推荐的波峰焊曲线 Recommended wave solder profile



- 推荐的焊膏类型 Recommended solder alloy: 96.5Sn/3.0Ag/0.5Cu

■ 修訂履歷 Revision History

版本Version	日期Date	修訂內容 Change Description	修改確認 Checked by
V1.0	2020-08-13	- 原版 The original version.	盧振强 Zhenqiang Lu
V2.0	2022-02-25	- 附錄中“包裝數量”：修改0201尺寸為15K包裝數量。 Revise the quantity of 0201 15Kpcs to Packaging Quantity.	杜建業 Jianye Du
V3.0	2022-06-16	- 修改產品標記由數碼體改為手寫體。 Modify the product marking from digital to handwritten. - “品名構成”、“額定值”增加1/2W參數。 Add the parameter 1/2W to Type Designation and Ratings.	杜建業 Jianye Du 李小雯 Xiaowen Li
V4.0	2023-02-20	- 附錄：增加RH-MY04, RH-MY08產品編帶包裝參數。 Appendix: Add the taping parameters of RH-MY04, RH-MY08. - 附錄：修改0201,0402,0603,0805編帶包裝A,B,T參數。 Appendix: Modify the taping parameters A,B,T of 0201,0402,0603,0805.	盧振强 Zhenqiang Lu

注：上述所提供之內容為產品規格說明。在產品未變更時，風華保有修改此內容不另行通知之所有權利，任何產品變更將會以PCN通知客戶。

Remark: Information provided above is intended to indicate product specifications only. Fenghua reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.