

# **JEDEC STANDARD**

---

## **Serial Flash Reset Signaling Protocol**

---

### **JESD252.01**

(Minor editorial revision to JESD252, October 2018)

**APRIL 2021**

---

**JEDEC SOLID STATE TECHNOLOGY ASSOCIATION**



## NOTICE

JEDEC standards and publications contain material that has been prepared, reviewed, and approved through the JEDEC Board of Directors level and subsequently reviewed and approved by the JEDEC legal counsel.

JEDEC standards and publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for use by those other than JEDEC members, whether the standard is to be used either domestically or internationally.

JEDEC standards and publications are adopted without regard to whether or not their adoption may involve patents or articles, materials, or processes. By such action JEDEC does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the JEDEC standards or publications.

The information included in JEDEC standards and publications represents a sound approach to product specification and application, principally from the solid state device manufacturer viewpoint. Within the JEDEC organization there are procedures whereby a JEDEC standard or publication may be further processed and ultimately become an ANSI standard.

No claims to be in conformance with this standard may be made unless all requirements stated in the standard are met.

Inquiries, comments, and suggestions relative to the content of this JEDEC standard or publication should be addressed to JEDEC at the address below, or refer to [www.jedec.org](http://www.jedec.org) under Standards and Documents for alternative contact information.

Published by  
©JEDEC Solid State Technology Association 2018  
3103 North 10th Street  
Suite 240 South  
Arlington, VA 22201-2108

JEDEC retains the copyright on this material. By downloading this file the individual agrees not to charge for or resell the resulting material.

**PRICE: Contact JEDEC**

Printed in the U.S.A.  
All rights reserved

PLEASE!

DON'T VIOLATE  
THE  
LAW!

This document is copyrighted by JEDEC and may not be reproduced without permission.

For information, contact:

JEDEC Solid State Technology Association  
3103 North 10th Street  
Suite 240 South  
Arlington, VA 22201-2107

or refer to [www.jedec.org](http://www.jedec.org) under Standards-Documents/Copyright Information.



## SERIAL FLASH RESET SIGNALING PROTOCOL

### Contents

---

Foreword.....	ii
Introduction.....	ii
1 Scope.....	1
2 Normative reference.....	1
3 Terms and definitions.....	1
4 Protocol Description.....	2
4.1 Reset Request.....	2
4.2 Reset Completion.....	2
4.3 Timing Diagram and Timing Parameters.....	2
4.4 Additional Notes and Considerations for the Protocol.....	3
Annex A (informative) Differences between revisions.....	4

---

## Foreword

---

This standard is intended for use by SoC, ASIC, ASSP, and FPGA developers or vendors interested in incorporating a signaling protocol for hardware resetting the Serial Flash device. It is also intended for use by peripheral developers or vendors interested in providing Serial Flash devices compliant with the standard.

This document was prepared by the JC-42.4\_3 Serial Flash task group authorized by the JC-42.4 Non-Volatile Memory subcommittee.

---

## Introduction

---

This standard defines a signaling protocol that allows the host to reset the targeted Serial Flash device without a dedicated hardware reset pin.

Some Serial Flash devices provide a dedicated RESET# pin that can be used to perform a hardware reset on the device. In such case, when the host asserts RESET# for a specified amount of time, the device will be reset in hardware.

Some Serial Flash devices may not provide such RESET# hardware pin for the function, either due to the size of the package or the pin is shared with an I/O pin by design. In the pin sharing situation, the reset function is disabled if the I/O pin is used in Quad or Octal configuration. Additionally, even if a RESET# hardware pin is available at the Serial Flash device, dedicating a host IO pin for controlling the RESET# signal may not be possible.

This standard specifies a signaling protocol that can be implemented on the Serial Flash interface to perform a hardware reset without a dedicated hardware RESET# pin. If both the host and the device support such protocol, the user can perform a hardware reset function by using only the CS#, SCK, and the SI pins.

## SERIAL FLASH RESET SIGNALING PROTOCOL

(From JEDEC Board Ballot JCB-17-46, formulated under the cognizance of the JC-42.4 Subcommittee on Non-Volatile Memory Devices.)

---

### 1 Scope

---

This standard specifies the signaling protocol for hardware resetting a Serial Flash device. The protocol can be used in the absence of or in addition to a dedicated RESET# pin on the device.

---

### 2 Normative Reference

---

The following normative documents contain provisions that through reference in this text, constitutes provisions of this standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated. For undated references, the latest edition of the normative document referred to applies.

JEDEC Manual, JM7.01, *Style Manual for Standards and Other Publications of JEDEC*.

JEDEC Standard, JESD88E, *Dictionary of Terms for Solid-State Technology*.

JEDEC Standard, JESD99C, *Terms, Definitions, and Letter Symbols for Microelectronic Devices*.

JEDEC Standard, JESD100B.01, *Terms, Definitions, and Letter Symbols For Microcomputers, Microprocessors, and Memory Integrated Circuits*.

JEDEC Standard, JESD216, *Serial Flash Discoverable Parameters (SFDP)*.

JEDEC Standard, JESD251, *eXpanded Serial Peripheral Interface (xSPI) for Non-Volatile Memory Devices*

---

### 3 Terms and Definitions

---

The current version of JESD88, *Dictionary of Terms for Solid-State Technology*, is the governing document for terms used in this standard. The following terms and definitions are provided for ease of reference:

**CS#:** Device Chip Select.

**IO0:** Serial Input and Output zero (some older devices refer to this signal as SI).

**IO1:** Serial Input and Output one (some older devices refer to this signal as SO).

**SCK:** Device Serial Clock.

## 4 Protocol Description

The Reset Signaling Protocol is shown in Figure 1 and described as follows:

The protocol consists of two phases: reset request, and completion (a device internal reset).

### 4.1 Reset Request

1. CS# is driven active low to select the SPI target (Note 1),
2. Clock (SCK) remains stable in either a high or low state (Note 2),
3. SI / IO0 is driven low by the bus initiator, simultaneously with CS# going active low, (Note 3), and
4. CS# is driven inactive (Note 4).

Repeat the steps 1-4 each time alternating the state of SI (Note 5).

NOTE 1 This powers up the SPI target.

NOTE 2 This prevents any confusion with a command, as no command bits are transferred (clocked).

NOTE 3 No SPI bus target drives SI during CS# low before a transition of SCK, i.e., target streaming output active is not allowed until after the first edge of SCK.

NOTE 4 The target captures the state of SI on the rising edge of CS#.

NOTE 5 SI is low on the first CS#, high on the second, low on the third, high on the fourth (This provides a 5h pattern, to differentiate it from random noise).

### 4.2 Reset Completion

After the fourth CS# pulse, the target triggers its internal reset.

### 4.3 Timing Diagram and Timing Parameters




Figure 1 — Reset Signaling Protocol



#### 4.3 Timing Diagram and Timing Parameters (cont'd)

**Table 1 — Timing Parameters**

<b>Parameter</b>	<b>Min</b>	<b>Max</b>	<b>Units</b>
tCSL	500	--	ns
tCSH	500	--	ns
Setup Time	5	--	ns
Hold Time	5	--	ns

#### 4.4 Additional Notes and Considerations for the Protocol

NOTE 1 This reset sequence is not intended to be used at normal power up.

NOTE 2 This reset sequence will be operational from any state that the device may be in.

NOTE 3 During the reset process, the device may ignore any commands.

ShanghaiQihuiTechnologyLtd.

## **Annex A (informative) Differences between revisions**

This annex briefly describes most of the changes made to entries that appear in this standard, JESD252.01, compared to its predecessor, JESD252 (October 2018). If the change to a concept involves any words added or deleted (excluding deletion of accidentally repeated words), it is included. Some punctuation changes are not included.

<b>Clause</b>	<b>Description of change</b>
---------------	------------------------------

3	Removed Term and definition for Si, replaced with term and definition for SCK.
---	--

“These changes have been made to comply with the JEDEC Standard Language/Terminology Directive, January 2021.

ShanghaiQihutTechnologyLtd



Standard Improvement Form

JEDEC

The purpose of this form is to provide the Technical Committees of JEDEC with input from the industry regarding usage of the subject standard. Individuals or companies are invited to submit comments to JEDEC. All comments will be collected and dispersed to the appropriate committee(s).

If you can provide input, please complete this form and return to:

JEDEC  
Attn: Publications Department  
3103 North 10<sup>th</sup> Street  
Suite 240 South  
Arlington, VA 22201-2107

Email : [juliec@jedec.org](mailto:juliec@jedec.org)

1. I recommend changes to the following:

Requirement, clause number \_\_\_\_\_

Test method number \_\_\_\_\_ Clause number \_\_\_\_\_

The referenced clause number has proven to be:

Unclear  Too Rigid  In Error

Other \_\_\_\_\_

2. Recommendations for correction:

---

---

---

---

3. Other suggestions for document improvement:

---

---

---

---

Submitted by

Name: \_\_\_\_\_

Phone: \_\_\_\_\_

Company: \_\_\_\_\_

E-mail: \_\_\_\_\_

Address: \_\_\_\_\_

City/State/Zip: \_\_\_\_\_

Date: \_\_\_\_\_

**JEDEC**<sup>®</sup>

ShanghaiQihuiTechnologyLtd.